

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2002-187343

(43)Date of publication of application : 02.07.2002

(51)Int.Cl.

B41M 5/00

B41J 2/01

C09D 11/00

(21)Application number : 2001-300188

(71)Applicant : TOYO INK MFG CO LTD

(22)Date of filing : 28.09.2001

(72)Inventor : YOSHIHIRO YASUO
NAKANO KAORI
FUSE YOSHIHIRO

(30)Priority

Priority number : 2000308613 Priority date : 10.10.2000 Priority country : JP

(54) MANUFACTURING METHOD FOR PRINTED MATTER

(57)Abstract:

PROBLEM TO BE SOLVED: To print a desired printed matter by a method wherein a uniform dot diameter is obtained on a synthetic resin base material by ink jet printing.

SOLUTION: This printed matter is obtained by executing an ink jet printing with an active energy ray curing type ink, which includes a pigment, a two or more ethylenic double bond-containing compound and a one ethylenic double bond-containing compound, has a surface tension of 25 to 40 mN/m and a viscosity of 10 to 50 mPa.s, after the printing surface of a synthetic resin base material is corona-treated or plasma-treated so as to develop the surface free energy of 65 to 72 mN/m.

LEGAL STATUS

[Date of request for examination] 09.06.2005

[Date of sending the examiner's decision of rejection] 05.06.2007

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection] 2007-017846

[Date of requesting appeal against examiner's decision of rejection] 27.06.2007

[Date of extinction of right]